

PATENTS ABSTRACTS OF JAPAN

E-1290 November 12, 1992Vol. 16/No. 542

(54) RECEPTION/EMISSION COMPOUND ELEMENT

(11) 4-207079 (A) (43) 29.7.1992 (19) JP



(21) Appl. No. 2-340487 (22) 30.11.1990

(71) HITACHI LTD (72) YOSHIKI YAZAWA(2)

(51) Int. Cl.⁶ H01L27/15, G11B7/135, H01L27/04, H01L27/14, H01L31/12, H01L33/00, H01S3/18, H04N1/024, H04N1/028

PURPOSE: To enable a light-emitting element and a light-receiving element to be compound in a simple structure by setting a light-emitting diode or a main terminal of one of a laser diode and a photo diode to a common potential without using a wiring.

CONSTITUTION: A p-type conductive type silicon is used as a first semiconductor substrate 1 and an n-type impurities layer where phosphor or arsenic is doped is formed as a second conductive type impurities layer 2. A double-layer gallium arsenide layer is formed on this n-type impurities layer 2, an impurities layer 6 at a side which contacts an Si substrate is formed as an n-type impurities layer by doping silicon or tellurium, and then beryllium or zinc is doped to an impurities layer 7 on it, thus forming a p-type impurities layer. A pn junction between the p-type Si substrate 1 and the n-type impurities layer 2 is formed as a photo diode and is used as a light-receiving element. A light-emitting diode is formed by the n-type impurities layer 6 and the p-type impurities layer 7 of GaAs and is used as a light-emitting element and an electrode which is formed on a from a first main surface of the Si substrate 1 to the n-type impurities layer 2 is used as a common electrode 8.



LEGENDE zu den Bibliographiedaten

(54) Titel der Patentanmeldung

(11) Nummer der JP-A2 Veröffentlichung

(21) Aktenzeichen der JP-Anmeldung

(43) Veröffentlichungstag

(22) Anmeldetag in Japan

(71) Anmelder

(52) Japanische Patentklassifikation

(51) Internationale Patentklassifikation